

PowerWalker VI 500-750 R1U Series



- Line Interactive model designed for 19" rack cabinet
- Slim 1U design
- USB with Human Interface Device (HID) support and Intelligent Slot for communication
- Pure Sine Wave for wide range of applications and harsh environment
- Auto dimming screen (UPS is woken up with mute button)

BACKUP TIME


Model	25% load	50% load	75% load	100% load
VI 500 R1U	18.5min	10.3min	4.3min	0.8min
VI 750 R1U	17min	8.7min	4.1min	0.4min

PowerWalker VI R1U Series offers slim design, which is unique on the market. It occupies only 1U of rack cabinet, but what is more, it can be fitted into places never before available for UPSs. It could even fit under your TV table to protect your home theatre. Considering the fact that fan is completely switched off in normal operation and LCD dims automatically, neither noise nor LCD shine will disturb your experience. With pure sine wave output in battery mode it delivers high quality voltage for the equipment. HID support for USB port will allow communication with NAS without further compatibility issues.

TECHNICAL SPECIFICATION

SERIES	VI 500 R1U	VI 750 R1U
INPUT		
Power capacity	500VA / 300W	750VA / 450W
Voltage Range	165-290 VAC	
Frequency Range	45Hz - 55Hz	
OUTPUT		
Voltage Regulation	230VAC \pm 10%	
Pure Sine Wave Output	Yes	
THDv	\leq 3% Full Linear Load; \leq 5% Non-Linear Load	
Outlets	4x IEC C13	
Transfer Time	Typical 4ms	
COMMUNICATION AND CONNECTIONS		
LCD	Yes	
USB	Yes, with HID support	
RS232	Yes	
EPO	Yes	
Intelligent Slot	Yes, for SNMP Card 2	
Software	Yes, PowerWalker PowerSoft	
BATTERIES		
Batteries	2x 7Ah/6V	2x 9Ah/6V
Recharge Time	8h to 90%	
Half Load Backup Time	10.3min	8.7min

ACCESSORIES

Name	Picture
SNMP Card 2 Network Management Item Number: 10131008 EAN: 4260074980424	
Rack Mount Kit - RK6 Item Number: 10132003 EAN: 4260074980431	